

USE LINK Standard Product Spec Sheet

Model Name 产品型号	UG-EB-002	Last Update 更新日期	2017-10-20	Page/Total Pages 页 码/页数	1/1
--------------------	-----------	---------------------	------------	----------------------------	-----

<p>Product Photo 产品图</p>	Rated voltage 额定电压 [V]	AC 100V-240V
	Appl. Frequency 适用频率 [Hz]	50~60Hz
	Nominal power 标称功率范围[W]	8W±10%
	Power factor 功率因子	≥0.5
	Correlated Color temperature range 色温范围(CCT) [K]	3000-5700 (± 300K)
	Luminous flux 光通量[lm]	360 lm±10%
	Luminous per watt 发光效率 (lm/W)	≥40 lm/W
	Color Rendering Index (CRI) 演色	≥80
	Beam Angle 发光角度[°]	200°
	Smart lighting	WIFI+PIR+smart home APPcontrol
	Camera	1080P
	<p>Product Diagram</p>	Size 产品尺寸
Base 灯头适用尺寸		E27
Net Weight 产品重量		222g
Packing 包装方式		box: 134*134*147mm(1PCS)
		cartoon: 419*282*330mm(12PCS)
Operating temperature range 温度范围 [°C] 工作		0~45°C
LED Lifetime		1年
Service life	10000hrs	

Camera specifications

Operation Sytem	Operation Sytem	Embedded Linux
Sensor	Sensor	AR0237
感光面积	sensor area	1/2.7 inch
焦距	focus length	0.95mm
视角	angle	Diagonal185° , horizontal185° , vertical185°
网络	network	Build-in WIFI 802.11b/g/n
Storage extension	Storage extension	Support 64GB Micro SD
Video压缩方式	compression	MPEG/H.264
Video成像颜色	imaging color	Color
Video分辨率	Resolution	1080p@30fps (1920*1080)
Video帧速率	frame frequency	5 ~ 30帧
云服务	cloud service	mobile phone 、 ipad
服务器	Sever	Support worldwide countries to keep stable working
喇叭	Speaker	8Ω 0.5W
存储温度	Storage Temperature	-20°C-45°C
麦克风	Microphone	-25dB

PIR specifications

感应角度	Induction angle	Horizontal90° , vertical90°
感应距离	Induction distance	5m
延迟时间	delay time	6~600sec